



LABOR RELATIONS DIVISION

401 Broadway NE
Albuquerque, NM 87102
Phone: 505-841-4400
Fax: 505-841-4424

226 South Alameda Blvd
Las Cruces, NM 88005
Phone: 575-524-6195
Fax: 575-524-6194

WWW.DWS.STATE.NM.US

Wage Decision Approval Summary

1) Project Title: Microsurfacing/ Road Repair in Town of Hagerman PO 288924 CES KCB
Requested Date: 05/28/2024
Approved Date: 05/29/2024
Approved Wage Decision Number: CH-24-1889-A

Wage Decision Expiration Date: 09/26/2024

2) Physical Location of Jobsite for Project:
Job Site Address: W Morgan St. to Mono Ave
Job Site City: Hagerman
Job Site County: Chaves

3) Contracting Agency Name (Department or Bureau): Town of Hagerman
Contracting Agency Contact's Name: Kami Mason
Contracting Agency Contact's Phone: (575) 752-3204 Ext.

4) Estimated Contract Award Date: 04/08/2024

5) Estimated total project cost: \$386,950.54
a. Are any federal funds involved?: No
b. Does this project involve a building?: No
c. Is this part of a larger plan for construction on or appurtenant to the property that is subject to this project?: No
d. Are there any other Public Works Wage Decisions related to this project?: No
e. What is the ultimate purpose or functional use of the construction once it is completed?:
Microsurfacing / road repair for W Morgan St to Mono Rd. (1.0m). Pavement rehabilitation using Type II polymer modified slurry seal on existing roadways. Total length of proposed project is 4.27 miles.

6) Classifications of Construction:

Classification Type and Cost Total	Description
Highway/Utilities (A) Cost: \$386,950.54	Mobilization or demobilization, delivery charge for equipment, hauled on 50-ton capacity towed trailer 50-ton capacity. Micro surfacing, Type II - MSE (20lbs/sy, 1/4" 18% micro surfacing emulsion), roadway. Mobilization and to the temporary yard set up to houses materials and vehicles. Cleaning and sweeping of the roadways will occur. After the roads are cleared, we will begin the application of type II micro surfacing which shall be a mixture of aggregate, asphalt emulsion, water, and other additives mixed and placed on the paved surface. Micro surfacing shall produce a cured mixture with a homogeneous appearance, a firm surface adhesion, and a skid resistance texture.