



**LABOR RELATIONS DIVISION**

401 Broadway NE  
Albuquerque, NM 87102  
Phone: 505-841-4400  
Fax: 505-841-4424

226 South Alameda Blvd  
Las Cruces, NM 88005  
Phone: 575-524-6195  
Fax: 575-524-6194

**WWW.DWS.STATE.NM.US**

**Wage Decision Approval Summary**

1) Project Title: SLHS Floor Covering 2023-4987 BH  
Requested Date: 07/17/2023  
Approved Date: 07/18/2023  
Approved Wage Decision Number: BE-23-1991-B

**Wage Decision Expiration Date for Bids: 11/15/2023**

2) Physical Location of Jobsite for Project:  
Job Site Address: 524 Central Ave SW  
Job Site City: Albuquerque  
Job Site County: Bernalillo

3) Contracting Agency Name (Department or Bureau): Siembra Leadership High School  
Contracting Agency Contact's Name: Katie Shelton  
Contracting Agency Contact's Phone: (505) 524-3440 Ext.

4) Estimated Contract Award Date: 07/01/2023

5) Estimated total project cost: \$69,060.04  
a. Are any federal funds involved?: No  
b. Does this project involve a building?: Yes - Siembra Leadership High School  
c. Is this part of a larger plan for construction on or appurtenant to the property that is subject to this project?: No  
d. Are there any other Public Works Wage Decisions related to this project?: No  
e. What is the ultimate purpose or functional use of the construction once it is completed?: Demolition and removal of old carpet and it's adhesive. New carpet tiles will replace the old ones, along with new adhesive. Moving of any furniture will be included prior to the removal of the old carpet. A 4" cove base and 4.5" of Johsonite Pebble will be installed. A skim coating will be applied and patching will also take place.

6) Classifications of Construction:

| Classification Type and Cost Total                      | Description  |
|---|--|
| <b>General Building (B)</b><br><b>Cost: \$69,060.04</b> | Demolition and removal of old carpet and it's adhesive. New carpet tiles will replace the old ones, along with new adhesive. Moving of any furniture will be included prior to the removal of the old carpet. A 4" cove base and 4.5" of Johsonite Pebble will be installed. A skim coating will be applied and patching will also take place. |